

D - Mark Adsorball® Carbon V-Bank Filter

D-Mark **Adsorball** Bulk Carbon V-Bank Honeycomb filter is designed to allow high volumes of activated carbon, or 50/50 carbon and activated alumina blends to be efficiently installed into new and existing HVAC systems.

Adsorball is designed for odor removal from spaces with heavier concentrations of unwanted gases. The industrial strength frame holds 24lbs – 35lbs of activated or impregnated carbon granules for commercial and industrial environments.

Gas adsorbing media (granules) are selected specifically to neutralize target gasses and remove those gases from the airstream. Fits most HVAC systems or easy retrofit.

Adsorball Plus combines 50% high activity carbon with 50% activated alumina with 5 % potassium permanganate to neutralize specific gasses such as ammonia, sulfur dioxide, hydrogen sulfide, and diesel fumes.

Custom or specific blends are available to neutralize target gasses.



Partial List of Contaminants Effectively Removed with Carbon

Industrial Process	Greenhouse
Adhesives	Organic Chemicals
Asphalt Fumes	Ozone
Cooking Odors	Perspiration
Disinfectants	Animal Odors
Food Aromas	Sewer Odors
Hospital Odors	Vapors
Irritants	Waste Products
Helipads	Diesel Exhaust
Airports	Paper Mills

Product Part Number	Nominal Size	Actual Size	GAC Weight Pounds	Initial Resistance (in w.g.)
AAC-12-100-01	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	11	0.25
AAC-12-100-06	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	20	0.25
AAC-12-100-08	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	24	0.25


			Plus 50/50 Pounds	
AAP -12-100-01	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	13	0.28
AAP -12-100-06	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	24	0.28
AAP - 12-100-08	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	29	0.28

Adsorball® Bulk Carbon V - Bank Filter

RENSA FILTRATION

Adsorball® Carbon V - Bank Filter

Performance Data




Description

Adsorball V- Bank Honeycomb filter is filled with 100% 6 x 12 mesh industrial grade 60 CTC High Activity Carbon for organic and specific molecular - gas phase control


Adsorball Plus V- Bank Honeycomb filter is filled with 50% 60 CTC carbon and 50% Activated Alumina with 5 % Potassium Permanganate

Frame: Double walled high - strength plastic frame for industrial applications


Sealant: Moisture resistant adhesive for continuous seal and pack strength



Industrial Grade Plastic Frame with Double Wall Construction



Carbon Granules
Suspended in Honeycomb
Matrix



Carbon and Potassium
Blend for Target Gases



Food Odor



Restaurant



Hospital



Greenhouse



Animal Odor



Industry



Office



Sewer Gas



Sports Arena

D - Mark
130 N. Groesbeck Hwy.
Mt. Clements, MI 48043
www.dmarkinc.com

RENSA FILTRATION

800-343-3610
586-949-3610
F 586-949-4181
dmark@dmarkinc.com